



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

## HOUSTON Y

HANDLING IN A WET ENVIRONMENT WITH BASIC MECHANICAL PROTECTION



EN 388: 2016

TECHNICAL DATA



**ARDON®**  
**WORKWEAR**  
& OUTDOOR

# HOUSTON Y

HANDLING IN A WET ENVIRONMENT WITH BASIC MECHANICAL PROTECTION

## CODE

A4013

## MATERIAL

Lining: cotton  
Coating: nitrile (yellow)  
Thickness: 0,98 mm (in palm)

## SIZE(S):

8 / M – 10 / XL

## UNIT

pair

## PACKING

Units in carton: 240 pairs  
Units in polybag: 12 pairs  
Retail packing: N/A

## DIMENSIONS


Carton H x W x D (cm)  
Carton (cbm)

5	6	7	8	9	10	11	12
-	-	-	48x26x45	50x26x46	50x26x46	-	-
-	-	-	0,0562	0,0598	0,0598	-	-

## WEIGHT

Carton (kg)  
Unit (g)

5	6	7	8	9	10	11	12
-	-	-	11,5	14,0	15,5	-	-
-	-	-	45,0	50,0	55,0	-	-



## Size chart (cm)

Total length (A)  
Cuff length (B)  
Cuff width (C)  
Palm width (D)

5	6	7	8	9	10	11	12
-	-	-	23,0	23,5	25,0	-	-
-	-	-	6,50	7,00	7,50	-	-
-	-	-	6,50	6,50	6,50	-	-
-	-	-	9,50	10,0	11,0	-	-

Tolerance (A)  $\pm 0,50$  (cm)  
Tolerance (B)  $\pm 0,50$  (cm)

Tolerance (C)  $\pm 0,50$  (cm)  
Tolerance (D)  $\pm 0,50$  (cm)

## DESCRIPTION

Cotton knit dipped in nitrile.

## STANDARDS

(EU) 2016/425

**EN ISO 21420:2020** Protective gloves – general requirements and test methods

**EN 388:2016 + A1:2018** Protective gloves against mechanical risks

EN 388



### PROTECTION LEVELS

#### MECHANICAL RISKS

abrasion resistance  
cut resistance  
tearing resistance  
puncture resistance  
cut resistance acc. to ISO

LVL	score	unit
2	500 – 2.000	cycles
X	not measured	index
1	10 – 25	N
1	20 – 60	N
X	not measured	N

### SPECIAL FEATURES

- 3/4 dipped
- elastic cuff knit



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

**Basic packaging (without sales label)**

A4013/08  
A4013/09  
A4013/10

**EAN**

8592390035226  
8592390035257  
8592390035264