



ARDON®
WORKWEAR
& **OUTDOOR**

DAVIS

HANDLING IN DRY ENVIRONMENT WITH LOW TEMPERATURE PROTECTION



EN 388: 2016

TECHNICAL DATA



ARDON®
WORKWEAR
& OUTDOOR

DAVIS

HANDLING IN DRY ENVIRONMENT WITH LOW TEMPERATURE PROTECTION

CODE

A9094

MATERIAL

Lining acrylic 7G (yellow)
Coating latex (blue)
Thickness 3,0 mm (in palm)

SIZE(S):

8 / M, 10 / XL, 11 / 2XL

UNIT

pair

PACKING


Units in carton 60 pairs
Units in polybag 12 pairs
Retail packaging sales label

DIMENSIONS

	5	6	7	8	9	10	11	12
Carton H x W x D (cm)	-	-	-	58x28x24	-	58x28x24	58x28x24	-
Carton (cbm)	-	-	-	0,0390	-	0,0390	0,0390	-

WEIGHT

	5	6	7	8	9	10	11	12
Carton (kg)	-	-	-	7,000	-	7,100	7,300	-
Unit (g)	-	-	-	117,0	-	118,0	121,0	-



Size chart (cm)

	5	6	7	8	9	10	11	12
Total length (A)	-	-	-	24,0	-	26,0	27,0	-
Cuff length (B)	-	-	-	7,50	-	8,40	9,00	-
Cuff width (C)	-	-	-	8,00	-	8,40	8,50	-
Palm width (D)	-	-	-	10,0	-	10,8	11,0	-

Tolerance (A) $\pm 0,50$ (cm)

Tolerance (B) $\pm 0,30$ (cm)

Tolerance (C) $\pm 0,30$ (cm)

Tolerance (D) $\pm 0,30$ (cm)

DESCRIPTION


Winter gloves made of acrylic knitted fabric dipped in latex with anti-slip finish.

STANDARDS

(EU) 2016/425

EN ISO 21420:2020 Protective gloves – general requirements and test methods

EN 388:2016 + A1:2018 Protective gloves against mechanical risks

	PROTECTION LEVELS			
	MECHANICAL RISKS			
		LVL	score	unit
	abrasion resistance	2	500 – 2.000	cycles
	cut resistance	1	1,2 – 2,5	index
	tearing resistance	2	25 – 50	N
	puncture resistance	X	not measured	N
	cut resistance acc. to ISO	X	not measured	N

SPECIAL FEATURES

- half-dipped winter gloves with insulation and anti-slip finish
- each pairs is retail ready packed



ARDON®
WORKWEAR
& OUTDOOR

Retail packaging (with sales label)

A9094/08
A9094/10
A9094/11

EAN

8592390039194
8592390039200
8592390012517

HEM COLOR

yellow
black
green

