



ARDON®
WORKWEAR
& OUTDOOR

ARDON® M60

SAFETY EARMUFFS ATTACHED TO THE SAFETY HELMET



TECHNICAL DATA SHEET



ARDON
WORKWEAR
& OUTDOOR

ARDON[®] M60

SAFETY EARMUFFS ATTACHED TO THE SAFETY HELMET

ARTICLE NO. C4007

MATERIAL ABS shell, PVC cushions,

WEIGHT 263 g

SNR 21 dB

DESCRIPTION

Safety earmuffs attached to the safety helmet

ATTENUATION:

SNR: 21 dB

High: 25

Medium: 19

Low: 11

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	---	10,3	12	18,6	29,5	30,8	29,5	26,6
Standard Deviation (dB)	---	3,8	3,5	2,8	3,2	4,2	4,5	6,4
APV: $M_f - s_f, \alpha = 1$	---	6,5	8,5	15,8	26,3	26,6	25	20,2



ARDON®
WORKWEAR
& OUTDOOR

STANDARDS

This personal protective equipment is in conformity with these harmonized European Standards:

EN 353-1:2002: Personal Hearing protectors: General requirements: Part3: Earmuffs attached to industrial safety helmet

Certified by notified body no. 2754 ALIENOR CERTIFICATION (ZA du Sanital – 21 Rue Albert Einstein - 86100 CHATELLERAULT - France), Certificate No.: N° 2754/2737/159/08/23/0735, issued on 1th of September 2023.

PIECES IN CARTON	20 pcs
WEIGHT OF A CARTON	16 kg
DIMENSIONS OF A CARTON	0,13 m ³
UNIT PACKING (POLYBAG)	1 pc

When worn properly and given adequate care, it provides excellent protection that filters high frequency noise which is found in most noise problems from dynamic machine such as workshop equipment, motor saws etc. Cleaning with warm soapy water, do not use organic solvents or alcohol for cleaning. It's required to disinfect the ear-muff every 3 months, according to the use. Any part of the ear muff which is in contact with the wearer shall be disinfected with a product suitable for use on plastics and not known to be harmful to the wearer. When not in use, it is recommended to store the ear muff in a clean and dry polybag. Always check the earmuff for damages before use. Any damaged / worn products should be discarded. The period of obsolescence of this product is 2 years.

