










| HS CODE   |
|---|
| 56090090  |
| CARTON SIZE / PCS.  |
| 40 x 40 x 24 / 10   |
| AET N° 2777/10965-01/E01-01   |
| <b>Satra Technology Europe Ltd., N° 2777,</b><br>Bracetown Business Park, Clonee,<br>Dublin, D15YN2P, Ireland |
| MODULE D FI14/14003.02  |
| <b>SGS Fimko Oy, N°0598</b><br>Takomotie 8,<br>00380 HELSINKI, Finland  |

|  |   |
|--|---|
| REF.   | FA 30 304 18  |
| LG.<br><br>KG | 1.8 m (connector included)<br>-----<br>Max. 100 KG  |
| CE   | EN 355:2002   |
| MAT.   |  30 mm<br>Polyester              |
|               | 35 mm   |
|               | <br>FA 50 101 17 / FA 50 207 55 |
|              | NO  |
| +  | ---   |
|             | 1.03 KG   |



**Largeur de l'absorbeur d'énergie**  
Width of the energy absorber  
**Ancho del absorbedor de energía**  
Larghezza del assorbitor di energia  
**Breite des Falldämpfers**

LG.



**Longueur Poids maxi utilisateur**  
**Length Max. user weight**  
**Longitud Peso máximo del usuario**  
**Lunghezza Peso Max. dell'utente**  
**Länge Höchstgewicht des Benutzers**



**Matière connecteur haut / connecteur bas**  
Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**



**Ouverture**  
Gate opening  
**Apertura**  
Apertura  
**Öffnung**



**Homologué pour le travail à proximité d'arêtes vives**  
Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**