










| HS CODE |
|---|
| 63079098 |
| CARTON SIZE / PCS. |
| 12 X 8 X 11.5 cm / 12 |
| AET N° 2777/10962-01/E01-01 |
| Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland |
| MODULE D FI14/14003.02 |
| SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland |

| | |
|--|---|
| REF. | FA 30 400 18 |
| LG.  | 1.8 m (connector included) ----- Max. 100 KG |
| CE | EN 355:2002 |
| MAT. |  30 mm Polyester |
|  | 35 mm |
|  |  FA 50 101 17 / FA 50 207 55 |
|  | NO |
| + | VG 11.063 |
|  | 1.65 KG |



Largeur de l'absorbeur d'énergie
Width of the energy absorber
Ancho del absorbedor de energía
Larghezza del assorbitor di energia
Breite des Falldämpfers

LG.



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
Material of top connector / bottom connector
Material conector alto / conector bajo
Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Ouverture
Gate opening
Apertura
Apertura
Öffnung



Homologué pour le travail à proximité d'arêtes vives
Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten