

## TECHNICAL DATA SHEET

### M5000


#### Eye protection

Article NO: E4044


Lens: clear  
 Material- lens: polycarbonate  
 Material- frame: polycarbonate



Extremely light safety glasses with rimless design which weights only 22 g. Panoramic visor made from a single piece fits perfectly to every type of face. Nose bridge is integrated and in the end of temples are holes for possibility of connection of cord. Clear lens are anti-fogging, anti-scratching and resistant to low-energy shocks (up to 45 m/s) at extreme temperatures (-5 °C - +55 °C).



Adjustable temple length - NO



Adjustable temple angle - NO



Anti-fogging lens - YES



Anti-scratching lens - YES

#### Clear lens, UV, 2-1.2 1 FT 0

Type of filter:	2	UV filter
Shade number:	1.2	clear
Optical class:	1	permanent use
Mechanical resistance:	FT	resistant to low-energy shocks at extreme temperatures
Type of the lens:	0	original lens



---

This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001: Personal eye protection. General requirements.

EN 170:2002: Personal eye-protection - Ultraviolet filters - Transmittance requirements and recommended use.

Certified by Notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands), Certificate no CE 749754, dated 26<sup>th</sup> August 2021.

---

Pieces in carton:	250
Pieces in box:	10
Polybag packing (pieces):	1
Carton weight:	12 kg
Carton size:	0,103 m <sup>3</sup>

---

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.

---