

TECHNICAL DATA SHEET

M8200


Eye protection

Article NO: E4056


Lens: yellow
 Material - lens: polycarbonate
 Material - frame: polycarbonate
 Material - temples: nylon



Very comfortable protective glasses. Soft transparent ventilated anti-slip nose bridge provides excellent wearing comfort throughout the day. Visor is wide and is made from one piece. Yellow visor is anti-fogging, anti-scratching and resistant to low-energy shocks (up to 45 m / s) even at extreme temperatures (-5 ° C - + 55 ° C).



Adjustable temple length - NO



Adjustable temple angle - NO



Anti-fogging lens - YES



Anti-scratching lens - YES

Yellow lens, 2-1.2 1 FT 0

Type of the filter:	2	UV filter
Shade number:	1.2	yellow lens
Optical class:	1	permanent use
Mechanical resistance:	FT	resistant to low-energy shocks at extreme temperatures
Type of the lens:	0	original lens



This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001: Personal eye protection. General requirements.

EN 170:2002: Personal eye-protection - Ultraviolet filters - Transmittance requirements and recommended use.

EN 172:2000: Personal eye protection - Sunlight filters for industrial use.

Certified by Notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands), Certificate no CE 749754, dated 26th August 2021.

Pieces in carton:	250
Pieces in box:	10
Polybag packing (pieces):	1
Carton weight:	11 kg
Carton size:	0,105 m ³

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.
