



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## ARDON® GANGERLOW S3

SAFETY SHOES



**DEFUSE  
CONTROL**



**DRY AIR**



**WATER  
REPELLENT**

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

# ARDON® GANGERLOW S3

SAFETY SHOES

## ARTICLE

G3364

## MATERIAL

Upper Cowhide leather, thickness 1.8 - 2 mm, fabric  
Lining MESH-type laminated breathable fabric  
Sole EVA/rubber, bonded technology  
Toe cap 604 composite  
Plate Kevlar  
Insole ANATOMIC FOAM – anatomically shaped from EVA foam

## SIZE

35-51

## UNIT

pair

## PACKAGE

Units in a carton 10 pairs  
Units in a box 1 pair

## DIMENSIONS

	35-43	44-51
Carton H x W x D (cm)	33.5 x 43.5 x 61.5	38.5 x 45.5 x 66.5
Carton (cbm)	0,090	0,116

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	230	237	244	250	257	264	270	277	284	290	297	304	310	317	324	330	337
Foot length cm	22,5	23,2	23,9	24,5	25,2	25,9	26,5	27,2	27,9	28,5	29,2	29,9	30,5	31,2	31,9	32,5	33,2

## DESCRIPTION

Safety boots with uppers made of brushed NUBUK cowhide leather and fabric, with a hydrophobic treatment, reinforced toecap and heel area, with composite toecap and a flexible kevlar insole.



**ARDON®**  
**WORKWEAR**  
& OUTDOOR

## NORMS















(EU) 2016/425

EN ISO 20345:2011

Personal protective equipment - Safety footwear

Category:

S3 HRO SRC

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C	✓	
insulation of the bottom of the shoe against heat		
insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

<b>CODE</b>	<b>EAN</b>	<b>CARTON WEIGHT (KG)</b>	<b>UNIT WEIGHT (KG)</b>
G3364/35	8592390152275	11.50	1.150
G3364/36	8592390152282	11.70	1.170
G3364/37	8592390152299	11.90	1.190
G3364/38	8592390152305	12.20	1.220
G3364/39	8592390152312	12.60	1.260
G3364/40	8592390152329	12.80	1.280
G3364/41	8592390152336	13.30	1.330
G3364/42	8592390152343	13.35	1.335
G3364/43	8592390152350	13.95	1.395
G3364/44	8592390152367	15.15	1.515
G3364/45	8592390152374	15.50	1.550
G3364/46	8592390152381	15.80	1.580
G3364/47	8592390152398	16.10	1.610
G3364/48	8592390152404	16.50	1.650
G3364/49	8592390152411	16.90	1.690
G3364/50	8592390152428	17.20	1.720
G3364/51	8592390152435	17.40	1.740





**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**





**ARDON®**  
**WORKWEAR**  
& OUTDOOR

