



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## ARDON® XLIGHT YELLOW ESD S1P

SAFETY SHOES



**DEFUSE  
CONTROL**



**DRY AIR**



**NONMETALLIC**



**REFLECTIVE**



**ESD**



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

# ARDON® XLIGHT YELLOW ESD S1P

SAFETY SHOES

## ARTICLE

G3396

## MATERIAL

Upper

Breathable fabric / TPU

Lining

Laminated breathable fabric MESH

Sole

Phylon/rubber, glued technology

Toe cap

Nano composite

Plate

FENGTA Ultralight kevlar

Insole

ANATOMIC FOAM – anatomically shaped from EVA foam

## SIZE

36-48

## UNIT

pair

## PACKAGE

Units in a carton

10 pairs

Units in a box

1 pair

## DIMENSIONS

Carton H x W x D (cm)

36-40  
32,5 x 41,5 x 54,5

41-44  
34 x 44,5 x 57

45-48  
36,5 x 48,5 x 62

-

Carton (cbm)

0,074

0,086

0,110

-

Size EUR

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

Insole length mm

-	239	246	253	259	266	273	280	286	293	298	300	313	320	-	-	-
---	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---	---	---

Foot length cm

-	23,4	24,1	24,8	25,4	26,1	26,8	27,5	28,1	28,8	29,3	29,5	30,8	31,5	-	-	-
---	------	------	------	------	------	------	------	------	------	------	------	------	------	---	---	---

## DESCRIPTION

Ultralight safety shoe with a sporty cut, with a nano composite toe cap and an ultralight Kevlar soleplate, with an upper made of gray breathable fabric with a print.



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## NORMS

(EU) 2016/425

EN ISO 20345:2011

EN61340-5-1:2016

Personal protective equipment - Safety footwear  
 Protection of electronic devices from electrostatic  
 phenomena - General requirements

**Category:** S1P SRC ESD

### Categories

### EN ISO 20345

E - energy absorption in the heel area

✓



FO - resistance to oils and fuels

✓



A - antistatic footwear

✓



SRC - resistance to slipping on ceramic floor tiles with SLS  
 and on steel floors with glycerin

✓



WR - upper resistant to water



Safety toe cap for toe protection

✓



P - resistance to punctures (protective insole)

✓



SRA - slip resistance ceramic floor tiles with SLS



HRO - resistance to contact heatup to 300 °C



insulation of the bottom of the shoe against heat



insulation of the bottom of the shoe against the cold



Splatters of molten metal



ESD – shoe protects against electrostatic discharge and can  
 be used on EPA premises

✓



The shoes do not contain metal parts

✓



-

-

-



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3396/36	8592390165435	9,55	0,955
G3396/37	8592390165442	10,15	1,015
G3396/38	8592390165459	10,25	1,025
G3396/39	8592390165466	10,55	1,055
G3396/40	8592390165473	10,80	1,080
G3396/41	8592390165480	11,00	1,100
G3396/42	8592390165497	11,20	1,120
G3396/43	8592390165503	11,35	1,135
G3396/44	8592390165510	11,55	1,155
G3396/45	8592390165527	11,70	1,170
G3396/46	8592390165534	11,85	1,185
G3396/47	8592390165541	12,00	1,200
G3396/48	8592390165558	12,15	1,215



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**





**ARDON®**  
**WORKWEAR**  
& OUTDOOR

