

ARDON® GRINDLOW 02

OCCUPATIONAL SHOES



**DEFUSE
CONTROL**



DRY AIR



**WATER
REPELLENT**



ARDON®
WORKWEAR
& **OUTDOOR**

ARDON® GRINDLOW O2

OCCUPATIONAL SHOES

ARTICLE

G3398

MATERIAL

Upper

Lining

Sole

Insole

SIZE

UNIT

PACKAGE

Units in a carton

Units in a box

ACTION NUBUK - cow leather with polyurethane coating, hydrophobic treatment / textile
Laminated breathable fabric MESH
PU/rubber, two density direct injection

ANATOMIC FOAM – anatomically shaped from EVA foam

36-48

pair

10 pairs

1 pair

DIMENSIONS

Carton H x W x D (cm)

Carton (cbm)

36-39

31.5 x 41.5 x 61.5

0,0804

40-43

33.5 x 43.5 x 61.5

0,0896

44-48

37 x 43.5 x 64

0,103

Size EUR

Insole length mm

Foot length cm

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
-	237	243	250	257	263	270	277	283	290	297	303	310	317	-	-	-
-	23,2	23,8	24,5	25,2	25,8	26,5	27,2	27,8	28,5	29,2	29,8	30,5	31,2	-	-	-

DESCRIPTION

Work shoes with an upper made of ACTION NUBUK material - cow leather with a coating of polyurethane, hydrophobic treatment and made of textile. The sole made of PU/rubber material has anti-slip SRC properties and is resistant to contact heat up to 300°C.















NORMS

(EU) 2016/425

EN ISO 20347:2012

Category:

Personal protective equipment – Occupational footwear
O2 SRC HRO

Categories	EN ISO 20347	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection		
P - resistance to punctures (protective insole)		
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C	✓	
insulation of the bottom of the shoe against heat		
insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		



ARDON®
WORKWEAR
& **OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3398/36	8592390162519	11.05	1.105
G3398/37	8592390162526	11.10	1.110
G3398/38	8592390162533	11.45	1.145
G3398/39	8592390162540	11.85	1.185
G3398/40	8592390162557	12.55	1.255
G3398/41	8592390162564	12.95	1.295
G3398/42	8592390162571	13.25	1.325
G3398/43	8592390162588	13.90	1.390
G3398/44	8592390162595	14.50	1.450
G3398/45	8592390162601	14.80	1.480
G3398/46	8592390162618	15.10	1.510
G3398/47	8592390162625	15.60	1.560
G3398/48	8592390162632	17.10	1.710



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& **OUTDOOR**

