



ARDON®
WORKWEAR
& OUTDOOR

ARDON® LEO CUT 4C

HANDLING IN DRY ENVIRONMENT WITH HIGH CUT PROTECTION
 AND STATIC PROTECTION



EN 388: 2016



EN 16350



ARDON®
WORKWEAR
& OUTDOOR

ARDON® LEO CUT 4C

HANDLING IN DRY ENVIRONMENT WITH HIGH CUT PROTECTION
AND STATIC PROTECTION

CODE

A5022

MATERIAL

Lining

15G HPPE (High Performance Polyethylene) + Carbon Fiber
+ Spandex

Coating

polyurethane (grey), fingertips

Thickness

1,0 ± 0,2 mm (in palm)

SIZE(S):

6 / XS – 9 / L

UNIT

pair

PACKING

Units in carton

120 pairs

Units in polybag

12 pairs

To the vending

1 pair (/V1, "sock")

DIMENSIONS

Carton H x W x D (cm)

5	6	7	8	9	10	11	12
-	38x28x21	38x28x21	38x28x21	38x28x21	-	-	-
-	0,0223	0,0223	0,0223	0,0223	-	-	-


Carton (cbm)

WEIGHT

Carton (kg)

5	6	7	8	9	10	11	12
-	4,80	4,90	5,10	5,50	-	-	-
-	32,0	33,0	34,0	37,5	-	-	-

Unit (g)



Size chart (cm)

	5	6	7	8	9	10	11	12
Total length (A)	-	21,0	22,0	23,0	24,0	-	-	-
Cuff length (B)	-	6,70	6,90	7,20	7,60	-	-	-
Cuff width (C)	-	8,10	8,30	8,50	8,80	-	-	-
Palm width (D)	-	8,80	9,00	9,20	9,40	-	-	-

Tolerance (A) ± 0,50 (cm)

Tolerance (B) ± 0,70 (cm)

Tolerance (C) ± 0,70 (cm)

Tolerance (D) ± 0,70 (cm)

DESCRIPTION


Highly durable ESD cut-resistant knit with polyurethane fingertips dipping.

STANDARDS

(EU) 2016/425

EN ISO 21420:2020 Protective gloves – general requirements and test methods

EN 388:2016 + A1:2018 Protective gloves against mechanical risks

 EN 388	PROTECTION LEVELS			
	MECHANICAL RISKS	LVL	score	unit
	abrasion resistance	3	2.000 – 8.000	cycles
	cut resistance	4	10 - 20	index
	tearing resistance	4	> 75	N
	puncture resistance	X	not measured	N
	cut resistance acc. to ISO	C	10 - 15	N

EN 16350:2014

Protective gloves - general requirements and test methods
for antistatic properties



SPECIAL FEATURES

- ESD cut resistant gloves
- durable knit (4C cut resistance)
- ARDON® design:
 - mandatory information on inner label
 - reflective manufacturer's logo
- compatible with touch screens
- also available without polyurethane = PROOF CUT 4C (do not leave fingerprints)
- also available with polyurethane palm dipping = BUCK CUT 4C

Basic packaging (without sales label)

A5022/V1-06
A5022/V1-07
A5022/V1-08
A5022/V1-09

EAN

8592390181015
8592390181022
8592390181039
8592390181046

HEM COLOR

violet
yellow
green
orange

