



**ARDON®**  
**WORKWEAR**  
& OUTDOOR

## ARDON® LEADERLOW O2

OCCUPATIONAL SHOES



**DEFUSE  
CONTROL**




**DRY AIR**



**WATER  
REPELLENT**



**REFLECTIVE**



**NONMETALLIC**

TECHNICAL SHEET



**ARDON®**  
**WORKWEAR**  
& OUTDOOR

# ARDON® LEADERLOW O2

OCCUPATIONAL SHOES

## ARTICLE

**G3421**

## MATERIAL

Upper  
Lining  
Sole

NUBUCK - cow leather 1,8 - 2 mm, hydrophobic / fabric  
laminated breathable fabric MESH  
PU/PU, two-component direct injection

## Insole

ANATOMIC FOAM – anatomically shaped from EVA foam

## SIZE

## UNIT

## PACKAGE

Units in a carton  
Units in a box

36-48  
pair

10 pairs  
1 pair

## DIMENSIONS

Carton H x W x D  
(cm)  
Carton (cbm)

36-42	43-48
34 x 48 x 65	37 x 50 x 69
0,106	0,128

## Size EUR

## Insole length mm

## Foot length cm

35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
-	239	246	252	259	266	272	278	286	291	298	306	312	319	-	-	-
-	23,4	24,1	24,7	25,4	26,1	26,7	27,3	28,1	28,6	29,3	30,1	30,7	31,4	-	-	-

## DESCRIPTION

Work boot with an upper made of full grain natural leather Oily nubuck. Thanks to the increased water resistance of the upper material, it is suitable for outdoor operations even in more demanding climatic conditions. The shoes are equipped with a stable PU/PU injection sole with sufficient internal space for comfortable use.



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## NORMS















(EU) 2016/425

EN ISO 20347:2022

Personal protective equipment – Occupational footwear

Category

O2 CI FO SR

Categories	EN ISO 20347	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SR - Slip resistance on ceramic tile floors with glycerol	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection		
P - resistance to punctures (protective insole)		
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heat up to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold	✓	
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts	✓	
-		
-		
-		



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3421/36	8592390355140	12,62	1,262
G3421/37	8592390355157	12,90	1,290
G3421/38	8592390355164	13,54	1,354
G3421/39	8592390355171	13,60	1,360
G3421/40	8592390355188	13,94	1,394
G3421/41	8592390355195	14,58	1,458
G3421/42	8592390355201	15,28	1,528
G3421/43	8592390355218	16,16	1,616
G3421/44	8592390355225	16,52	1,652
G3421/45	8592390355232	17,12	1,712
G3421/46	8592390355249	17,18	1,718
G3421/47	8592390355256	17,25	1,725
G3421/48	8592390355263	17,35	1,735





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

