



**ARDON®**  
**WORKWEAR**  
& **OUTDOOR**

## ARDON® CREATRON®

COMFORTABLE HANDLING IN DRY ENVIRONMENT  
(WITH PROTECTION AGAINST CONTACT HEAT)



TECHNICAL DATA



EN 388: 2016



EN 407:2020



**ARDON®**  
**WORKWEAR**  
& OUTDOOR

# ARDON® CREATRON®

COMFORTABLE HANDLING IN DRY ENVIRONMENT  
(WITH PROTECTION AGAINST CONTACT HEAT)

## CODE

**A8027**

## MATERIAL

Lining  
Coating  
Thickness

Polyester 15G + sandy nitrile foam  
nitrile foam  
±1,1 mm (in palm)

## SIZE(S):

6 / XS – 11 / 2XL

## UNIT

pair

## PACKING

Units in carton  
Units in polybag  
Retail packing

120 pairs  
12 pairs  
sales label (-SPE)

## DIMENSIONS


Carton H x W x D (cm)  
Carton (cbm)

5	6	7	8	9	10	11	12
-	52*26*30	52*26*30	52*26*30	52*28*30	52*28*30	52*28*30	-
-	0,041	0,041	0,041	0,044	0,044	0,044	-

## WEIGHT

Carton (kg)  
Unit (g)

5	6	7	8	9	10	11	12
-	4,5	23	24	25	26	27	-
-	30,5	33	37,5	40,5	44,5	47,5	-



## Size chart (cm)

Total length (A)  
Cuff length (B)  
Cuff width (C)  
Palm width (D)

5	6	7	8	9	10	11	12
-	22	23	24	25	26	27	-
-	7,2	7,5	7,7	7,9	8,1	8,3	-
-	8	8,2	8,5	8,9	9,1	9,5	-
-	9	9,4	9,9	10,7	11,2	11,8	-

Tolerance (A) ± 0,50 (cm)  
Tolerance (B) ± 0,70 (cm)

Tolerance (C) ± 0,70 (cm)  
Tolerance (D) ± 0,70 (cm)

## DESCRIPTION

Polyester knit dipped in sandy nitrile foam, with sales label.

TECHNICAL DATA

## STANDARDS

(EU) 2016/425

**EN ISO 21420:2020** Protective gloves – general requirements and test methods

**EN 388:2016 + A1:2018** Protective gloves against mechanical risks

EN 388



### PROTECTION LEVELS

#### MECHANICAL RISKS

abrasion resistance  
cut resistance  
tearing resistance  
puncture resistance  
cut resistance acc. to ISO

#### LVL

4  
1  
2  
1  
A

#### score

>8000  
1,2 – 2,5  
25 – 50  
20 – 60  
2

#### unit

cycles  
index  
N  
N  
N

**EN 407:2020** Protective gloves against heat or flame

EN 407



### PROTECTION LEVELS

#### THERMAL RISKS

resistance to burning  
resistance to contact heat  
resistance to convective heat  
resistance to radiant heat  
resistance to small drops of molten metals  
resistance to large drops of molten metals

#### LVL

X  
2  
X  
X  
X  
X

#### score

not measured  
250°C for 15s  
not measured  
not measured  
not measured  
not measured

### SPECIAL FEATURES

- 3D breathable (also in the area of coating)
  - with contact heat protection
  - each pair in all sizes is automatically in retail packaging (retail ready)
  - ARDON® design:
    - manufacturer's logo
    - color coordinated with the clothing collection
- ARDON®CREATRON®** black neon



**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**

## Retail packaging (with sales label)

A8027/06-SPE  
A8027/07-SPE  
A8027/08-SPE  
A8027/09-SPE  
A8027/10-SPE  
A8027/11-SPE

## EAN

8592390361905  
8592390361912  
8592390361929  
8592390361936  
8592390361943  
8592390361950





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**



TECHNICAL DATA





**ARDON®**  
**WORKWEAR**  
**& OUTDOOR**



TECHNICAL DATA

